

# MS08B | 8-slot Compact Benchtop Mainframe



## Product Description

The MS08B is an 8-slot benchtop mainframe that is compatible to work with a customizable external computer\*. The MS08B communicates to the computer via an included PCI card running on Windows 10, Windows 8, Windows 7 or Windows XP.

The MS08B allows for both single-mode and multimode insertion loss and return loss testing within a single station. Different modular configurations can be setup for testing two to four wavelengths. Pairing a MS12 with a MS7 Optical Switch allows up to 48 channel multi-fiber testing in the single 8-slot mainframe. Cascading mainframes or pairing with an external SX8 switch available for higher channel count testing requirements.

## KEY FEATURES

- 8-slot mainframe
- Controlled by an external computer\*
- Compact
- Benchtop
- Windows 10, Windows 8, Windows 7 or Windows XP compatible

\* See minimum requirement

## APPLICATIONS

- Component testing
- Ribbon fiber testing
- Simultaneous testing with multiple connector types
- Incoming inspection
- QA testing
- Single and Multi Fiber Testing

## IN THE BOX

- MS08B
- PCI Card
- Power Cord

### JGR Optics Inc.

160 Michael Cowpland Dr.

Ottawa, Ontario K2M 1P6 CANADA

26 | T 613-599-1000 | F 613-599-1099 | info@jgroptics.com

WWW.JGROPTICS.COM



## Specifications

* MINIMUM COMPUTER REQUIREMENTS	
Operating System	32-bit and 64-bit compatible - Windows 10, Windows 8, Windows 7, or Windows XP
Case Size	Mid-Tower
Motherboard	1 available PCI slot
Hard Drive	At least 40GB free
Processor	2nd Generation Intel Core i3 or higher
RAM	4GB

MECHANICAL / ENVIRONMENTAL SPECIFICATIONS	
Parameter	Specification
Unit Dimensions W x H x D (cm)	47 x 15 x 34
Shipping Box Dimensions W x H x D (cm)	53 x 32 x 57
Unit Weight (kg)	7.5
Total Shipment Weight (kg)	8.5
Operating Temperature (°C)	0 to 40
Storage Temperature (°C)	-40 to 70
Humidity (Non-condensing) (°C)	Maximum 95% RH from 0 to 40

## Ordering Scheme

### **MS08B**

8-slot Compact Benchtop Mainframe