

MS12001 | System



Product Description

The MS12001 system provides the most accurate mandrel-free insertion loss and return loss measurement in the industry for both cable assemblies and optical components. The MS12001 system allows both single-mode and multimode insertion loss and return loss testing within a MS08B single station. The modular platform allows for simplex testing and easy future expansion into multi-fiber testing with the addition of a MS7 1xN optical switch. The MS12001 user-friendly software allows for new test configurations to be set up in seconds and saved for future use.

The software then manages all test sequences, databases and results.

KEY FEATURES

- Turn-key software
- Local / Remote Database
- Mandrel Free IL/RL
- Modular design providing flexibility and simplifying system upgrades

APPLICATIONS

- Component testing
- Ribbon fiber testing
- Simultaneous testing with multiple connector types
- Incoming inspection
- QA testing
- Single and Multi Fiber Testing

IN THE BOX

- MS05B or MS08B
- Power Cord

JGR Optics Inc.

160 Michael Cowpland Dr.
Ottawa, Ontario K2M 1P6 CANADA

19 | T 613-599-1000 | F 613-599-1099 | info@jgroptics.com

WWW.JGROPTICS.COM



MS12001 KEY FEATURES

- High-sensitivity, mandrel-free return loss up to 80 dB
- Simultaneous testing at four single-mode wavelengths (1310, 1490, 1550 and 1625 nm)
- Compatible with simplex, duplex, multifiber, bundle, hybrid and fan-out cable assemblies
- Turnkey software and database for manufacturing applications
- Testing capabilities for PLC splitters and planar arrays
- The MS12 meters are fully compatible with the IQS-3250 and IQS-3250B from EXFO

COMPLETE INTEGRATION TO MAXIMIZE PERFORMANCE

The MS12001 software has been designed to maximize efficiency in production while keeping its operation simple. Working closely with industry leaders the software can accommodate all current market requirements. The complete integration of the different system components provides the highest possible throughput for insertion loss (IL) and mandrel-free return loss (RL) testing.

GRAPHICAL USER INTERFACE

- Step-by-step instructions with connection diagrams
- Controls available from the main screen
- Live monitoring of IL and RL measurements



JGR Optics Inc.

160 Michael Cowpland Dr.
Ottawa, Ontario K2M 1P6 CANADA

20 | T 613-599-1000 | F 613-599-1099 | info@jgroptics.com

www.JGROptics.com



DATA POST-PROCESSING

- Integrated database with all necessary tools to manage results and build reports
- Customized label printing capability
- Database browser with filter builder

AUTOMATION OF CUSTOMER SPECIFIC TESTS

The MS12001 system comes with a full set of SCPI commands allowing customers to develop their own testing applications. The SCPI commands have been implemented to allow users to bypass just the right level of integration from the MS12001 system to develop applications like environmental testing but still benefit from the extensive signal processing capabilities of the system.


MSC Verification Tool

Wondering about the performance of your meter? Using JGR's MSC single-mode return loss module the user can easily verify if the system still meets meter specifications. A step by step process guides Supervisors to verify the equipment is working properly.


Multiple Configurations for Multiple Requirements

In its standard configuration, the MS12001 system includes only the hardware required to perform IL and return loss measurements at a minimal cost. By adding additional switch ports and loss meters, the MS12001 system can be configured for high-throughput applications in order to minimize handling and therefore reduce the testing time. When more than 72 channel switches are required, external switches (such as the JGR SX8 Switch) can be controlled using the GPIB interface. To save even more time, specific switch ports can be assigned to specific connector types eliminating the need to disconnect the launch fiber. For example, using a 1 x32 switch can allow you to dedicate channels 1 to 24 to MTP connectors (male and female), ports 25 to 28 to MT-RJ connectors (male and female), and still have room for FC, ST, SC and MU connectors.

Standard Configuration



High-Throughput Configuration



Accessories

The MS12001 system also supports a full range of accessories to further improve the testing time. The user's generic label printer, generic bar code reader and footswitch (pn: VIP-912-FS1) can be added to the system and its use is fully integrated in the software. The footswitch can be purchased from www.vetra.com/footsw2.htm. Should the user require the new license for VSVIEW 8.0 RE - ESD label editing, it can be purchased from www.componentone.com.

Ordering Scheme

MS05B

5-slot Compact Benchtop Mainframe

MS08B

8-slot Benchtop Mainframe

Specifications

MINIMUM COMPUTER REQUIREMENTS	
Operating System	32-bit and 64-bit compatible - Windows 10, Windows 8, Windows 7, or Windows XP
Case Size	Mid-Tower
Motherboard	1 available PCIe slot (1x, 4x, 8x or 16x)
Hard Drive	At least 40GB free
Processor	2nd Generation Intel Core i3 or higher
RAM	4GB

MECHANICAL/ENVIRONMENTAL SPECIFICATIONS		
Parameter	Specification	
	MS05B	MS08B
Unit Dimensions W x H x D (cm)	36 x 15 x 34	47 x 15 x 34
Shipping Box Dimensions W x H x D (cm)	43 x 27 x 47	53 x 32 x 57
Unit Weight (kg)	7	7.5
Total Shipment Weight (kg)	8	8.5
Operating Temperature (°C)	0 to 40	
Storage Temperature (°C)	-40 to 70	
Humidity (Non-condensing) (°C)	Maximum 95% RH from 0 to 40	